

MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet according to 91/155/EEC, the standards and regulatory requirements of United States. Date of issue: 01/09/2005



1. SUBSTANCE/PREPARATION AND COMPANY IDENTIFICATION

Product Name: EPDM ERIKS compound 55914 PC
MSDS N°: E0003
Chemical Name: Ethylene-Propylene elastomer
Company: ERIKS bv
Toermalijnstraat 5
1812 RL Alkmaar
Postbus 280, 1800 BK Alkmaar
Tel. +31 72 / 514 15 14
Fax +31 72 / 515 56 45
info@eriks.nl
www.eriks.nl
www.O-ring.info

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Nature (preparation)

Description:

Ethylene-Propylene-Ethylidene-Norbornene
Hydrocarbon elastomer (CAS number: 25038-36-2)

3. HAZARDS IDENTIFICATION

Potential Health Effects

Possible routes of entry include skin & eye contact and process vapor or dust inhalation.

Smokers should avoid contamination of tobacco products with product and should wash their hands before smoking.

4. FIRST AID MEASURES

Inhalation

If exposed to fumes from overheating or combustion, move to fresh air. Consult a physician if symptoms persist.

Skin Contact

Wash with soap and water.

Eye Contact

Flush eyes with plenty of water. Consult a physician if symptoms persist.

Ingestion

Not expected to occur during normal use of product.

MATERIAL SAFETY DATA SHEET

5. FIRE FIGHTING MEASURES

Extinguishing Media

Water, Foam, Dry Chemical, CO₂

Fire Fighting Instructions

Wear self-contained breathing apparatus. Wear full protective equipment.

Exposure Hazards

Decomposition products see section 10.



6. ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Spill Clean up

Sweep up to avoid slipping hazard.

7. HANDLING AND STORAGE

Handling

Protect against fire.

Storage

Store in cool, dry place away from direct light to maintain quality.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls**Ventilation:**

Vapors and fumes liberated from compounds during hot cured processing should be exhausted from work areas to maintain the ambient workplace atmosphere below the limits in section 2.

Personal Protective Equipment**Respirators:**

when temperature exceeds 200°C and ventilation is inadequate to maintain concentration below exposure limits, use a positive pressure air supplied respirator. Air purifying respirators may not provide adequate protection.

Protective Clothing:

If there is potential contact with hot/molten material, wear heat resistant clothing and footwear. Do not touch decomposed parts even when cool. Neoprene gloves recommended.

MATERIAL SAFETY DATA SHEET

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Data:

Melting Point: NA
 % Volatiles: NA
 Solubility in Water: Insoluble
 Odor: None
 Color: Black
 Appearance: Solid
 Specific Gravity: 1.12



10. STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperature and storage condition.

Conditions to avoid

Overheating

Incompaibility with other materials

No specific information is available, however strong oxidizers or reducing agents which generally not compatible with compounds.

Hazardous Decomposition Products

Fumes produced when heated to decomposition temperatures may contain carbon monoxide, carbon dioxide, hydrogen cyanide, oxides of nitrogen, and small amounts of aromatic and aliphatic hydrocarbons. Combustion products from rubber, like those of other natural and synthetic materials, must be considered toxic.

11. TOXICOLOGICAL INFORMATION

No information is available.

12. ECOLOGICAL INFORMATION

Aquatic toxicity: No information is available.

13. DISPOSAL CONSIDERATIONS

Waste disposal

Preferred options for disposal are (1) recycling, (2) incineration with energy recovery, and (3) landfill. The high fuel value of this product makes option 2 very desirable for material that cannot be recycled, but incinerator must be capable of scrubbing out acidic combustion products. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

MATERIAL SAFETY DATA SHEET

14. TRANSPORTATION INFORMATION

Shipping information

DOT

Proper shipping name: not regulated

Hazard class: not regulated



15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status: This product and all components are listed on U.S. EPA Toxic Substances Control Act Inventory and in accordance with EC directives/GefStoffV.

16. OTHER INFORMATION

Hazard Rating System Classifications:

	NFPA	HMIS	
Health:	2	0	National Fire Protection Association rating identifies hazards a fire emergency
Flammability:	1	1	Hazardous Materials Identification system rating applies to products as packaged
Reactivity:	0	0	

Key: 0=least; 1=slight; 2=moderate; 3=high; 4=extreme

Important Note:

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. This information is obtained from various sources including the manufacturer and other third party sources. The safety data sheet only describes the products in aspect to their safety requirements.

MATERIAL SAFETY DATA SHEET

FOR MORE INFORMATION:

THE NETHERLANDS

ERIKS bv
Toermalijnstraat 5
1812 RL Alkmaar
Postbus 280, 1800 BK Alkmaar
Tel. +31 72 / 514 15 14
Fax +31 72 / 515 56 45
info@eriks.nl
www.eriks.nl

BELGIUM

ERIKS nv
Boombekelaan 3
B-2660 Hoboken
Tel. +32 3 / 829 26 11
Fax +32 3 / 828 39 59
info@eriks.be
www.eriks.be

FRANCE

ERIKS sarl
52, avenue des Frères-Lumière BP 151
F-78196 Trappes cedex
Tel. +33 1 / 34 82 10 00
Fax +33 1 / 34 82 10 32
sce.clientele@eriks.fr

GERMANY

ERIKS Gruppe Deutschland
Brönninghauser Str. 38
33729 Bielefeld
Tel. +49 521/9399-0
Fax +49 521/9399-49
www.eriks.de

For more technical compound info, consult: www.O-ring.info

