

## MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet according to 91/155/EEC, the standards and regulatory requirements of United States. Date of issue: 01/09/2005



### 1. SUBSTANCE/PREPARATION AND COMPANY IDENTIFICATION

**Product Name:** VITON® compound 51414 green  
**MSDS N°:** V0009  
**Chemical Name:** Fluorinated Elastomer  
**Company:** ERIKS bv  
Toermalijnstraat 5  
1812 RL Alkmaar  
Postbus 280, 1800 BK Alkmaar  
Tel. +31 72 / 514 15 14  
Fax +31 72 / 515 56 45  
info@eriks.nl  
www.eriks.nl  
www.O-ring.info

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

#### Chemical Nature (preparation)

#### Description:

Vinylidene fluoride-hexafluoropropene polymer (CAS number: 9011-17-0)  
Material is not known to contain Toxic Chemicals under Section 313 of Title III of the Superfund amendments and Reauthorization Act of 1986 and 40 CFR part 372.

### 3. HAZARDS IDENTIFICATION

#### Potential Health Effects

Skin contact with material may cause skin with discomfort or rash. Significant skin permeation and systemic toxicity after contact appears unlikely. There are no reports of human sensitization.

Inhalation of fumes from burning polymer may cause temporary lung irritation effects with cough, discomfort, difficulty breathing, or shortness of breath. Higher exposures to fumes from burning material may cause pulmonary edema (body fluid in lungs) with cough, wheezing, abnormal lung sounds possibly progressing to severe shortness of breath and blush discoloration of the skin. Symptom may be delayed. Prompt medical attention is required.

Smokers should avoid contamination of tobacco products with polymer and should wash their hands before smoking.

#### Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0,1% are listed by IARC, NTP, OSHA, or ACGIH as a carcinogen.

## MATERIAL SAFETY DATA SHEET

### 4. FIRST AID MEASURES

#### Inhalation

If exposed to fumes from overheating or combustion, move to fresh air; Consult a physician if symptoms persist.

#### Skin Contact

Wash with soap and water.

#### Eye Contact

Flush eyes with plenty of water. Consult a physician if symptoms persist.

#### Ingestion

No specific intervention is indicated as compound is not likely to be hazardous by ingestion. Consult a physician if necessary.



### 5. FIRE FIGHTING MEASURES

#### Plammable properties

Flash point: > 204°C / 399°F

Method: Open cup

#### Fire and Explosion hazards

Hazardous gasses/vapors produced in fire are hydrogen fluoride (HF), carbonyl fluoride, carbon monoxide, low molecular weight fluorocarbons.

#### Extinguishing Media

Water, Foam, Dry Chemical, CO<sub>2</sub>

#### Fire Fighting Instructions

Wear self-contained breathing apparatus. Wear full protective equipment.

Does not burn without an external flame. Protect from hydrogen fluoride fumes which react with water to form hydrofluoric acid. Wear Neoprene gloves when handling refuse from a fire.

### 6. ACCIDENTAL RELEASE MEASURES

#### Safeguards (Personnel)

Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

#### Spill Clean up

Sweep up to avoid slipping hazard.

## MATERIAL SAFETY DATA SHEET

### 7. HANDLING AND STORAGE

#### Handling

Protect against fire.

#### Storage

Store in cool and dry place.



### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Engineering Controls

##### Ventilation:

Vapors and fumes liberated from compounds during hot cured processing should be exhausted from work areas to maintain hydrogen fluoride concentration below the PEL.

#### Personal Protective Equipment

##### Respirators:

when temperature exceeds 200°C and ventilation is inadequate to maintain concentration below exposure limits, use a positive pressure air supplied respirator. Air purifying respirators may not provide adequate protection.

##### Protective Clothing:

If there is potential contact with hot/molten material, wear heat resistant clothing and footwear. Do not touch decomposed parts even when cool. Neoprene gloves recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical Data:

Melting Point:	NA
% Volatiles:	NA
Solubility in Water:	insoluble
Odor:	None
Color:	Green
Appearance:	Solid
Specific Gravity:	2.07

## MATERIAL SAFETY DATA SHEET

### 10. STABILITY AND REACTIVITY

#### Chemical Stability

Stable at normal temperature and storage condition.

#### Conditions to avoid

Temperatures above 200°C

#### Incompatibility with other materials

Incompatibility with finely divided metals such as aluminium.  
Compounding with metal powders presents an explosion hazard.

#### Decomposition

Hazardous decomposition products: Hydrogen fluoride (HF) and perfluoroolefins.

If the finish part is used or tested at temperature above 316°C, the surface of the parts may contain HF or HF condensate, which may cause severe burns, sometimes with symptoms delayed for several hours. Wear Neoprene or PVC (if temperature is below melting point of PVC) gloves when handling parts or equipment after exposure to such high temperatures. If condensate is expected, wash equipment and parts well with limewater (calcium hydroxide solution). Discard gloves after handling degraded these parts.



### 11. ECOLOGICAL INFORMATION

#### Ecotoxicological information

Aquatic toxicity: No information is available.  
Toxicity is expected to be low based on insolubility in water.

### 12. DISPOSAL CONSIDERATIONS

#### Waste disposal

Preferred options for disposal are (1) recycling, (2) incineration with energy recovery, and (3) landfill. The high fuel value of this product makes option 2 very desirable for material that cannot be recycled, but incinerator must be capable of scrubbing out acidic combustion products. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

## MATERIAL SAFETY DATA SHEET

### 13. TRANSPORTATION INFORMATION

#### Shipping information

DOT

Proper shipping name: not regulated

Hazard class: not regulated



### 14. REGULATORY INFORMATION

#### U.S. Federal Regulations

TSCA Inventory Status: In compliance with TSCA Inventory requirements for commercial purposes.

State Regulations (U.S.): No substances on the state hazardous substances list are used in this compound.

### 15. OTHER INFORMATION

#### Additional Information

Medical use: Do not use in medical applications involving permanent implantation in human body.

#### Important Note:

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. This information is obtained from various sources including the manufacturer and other third party sources. The safety data sheet only describes the products in aspect to their safety requirements.

## MATERIAL SAFETY DATA SHEET

### FOR MORE INFORMATION:



#### THE NETHERLANDS



ERIKS bv  
Toermalijnstraat 5  
1812 RL Alkmaar  
Postbus 280, 1800 BK Alkmaar  
Tel. +31 72 / 514 15 14  
Fax +31 72 / 515 56 45  
info@eriks.nl  
www.eriks.nl

#### BELGIUM



ERIKS nv  
Boombekelaan 3  
B-2660 Hoboken  
Tel. +32 3 / 829 26 11  
Fax +32 3 / 828 39 59  
info@eriks.be  
www.eriks.be

#### FRANCE



ERIKS sarl  
52, avenue des Frères-Lumière BP 151  
F-78196 Trappes cedex  
Tel. +33 1 / 34 82 10 00  
Fax +33 1 / 34 82 10 32  
sce.clientele@eriks.fr

#### GERMANY



ERIKS Gruppe Deutschland  
Brönnighauser Str. 38  
33729 Bielefeld  
Tel. +49 521/9399-0  
Fax +49 521/9399-49  
www.eriks.de

For more technical compound info, consult: [www.O-ring.info](http://www.O-ring.info)