

# TPe RX® P350 - Technical Data Sheet

#### 1. Introduction

TPe RX® P350 is a SEBS thermoplastic elastomer with extreme low shore hardness.

### 2. Product Description

Chemical Composition:	SEBS (Styrene-ethylene-Butadiene-Styrene)	
Physical form :	Cord / Extrusions	
Color :	White	
Specific Weight :	1,01	
Storage stability * :	Excellent	

<sup>\*:</sup> Following ISO 2230 conditions





Animal Derived Ingredient

## 3. Physical Properties

Test Method	Norm	Test Values
Hardness	ISO 868	20° Shore A
Tensile Strength at break	ISO 527	1,7 Mpa
Elongation at break	ISO 527	500 %
Compression Set	ISO 815	
24h/23°C		10 %
24h/70°C		31 %

# T D T

### 4. Temperature Resistance

• -50° to +90°C

### 5. Advantages

- Alternative to EPDM or other rubber compounds
- Recycable
- Available in many colours
- Can be welded
- Can be glued (cyanoacrylate)
- Can be produced in small quantities
- Tolerances ISO 3302-E2
- Can be adhesive backed

### 6. Applications

- Replacement of cellular and spongerubber
- Excellent for food and pharmaceutical industry
- FDA 177.2600 and BGVV compliant
- Certificate on demand

### 7. Other Information

 This compound is ADI (Animal Derived Ingredient Free).



ERIKS

FRIKS

ERI

This information is, to the best of our knowledge, accurate and reliable to the date indicated. The above mentioned data have been obtained by tests we consider as reliable. We don't assure that the same results can be obtained in other laboratories, using different conditions by the preparation and evaluation of the samples.

01.10.2006



